



Natural NR/SBR

SPECIFICATION SHEET

Grade	N11E	
Colour	BLACK	
Elastomer	NR/SBR	
Quality	ECONOMY FINE FLUTED	
Hardness Shore A ±5	65°	ISO 7619-1
SG (g/cm²)	1.5	ISO 2781
Tensile (N/mm²)	2.5	ISO 37
Elongation %	200	ISO 37
Compression %	ISO 37	
Tear Strength	ISO 34-1	
Abrasion mm³	ISO 37	
Temperature (° C) from		
Temperature (°C) to		

Roll Tolerances

Thicknesses available

Width tolerance: +/- 2% ISO 3302 SW1
 Length tolerance: +/- 2% ISO 3302 SW1

3mm and 6mm .914m, 1m, 1.22m

Thickness

0.5– 1mm +/- 0.2mm
 1.5mm –3mm +/- 0.3mm
 4mm—5mm +/- 0.4mm
 6mm +/- 0.5mm
 8mm +/- 0.7mm
 10mm—15mm +/- 1mm
 20mm +/- 1.4mm
 25mm +/- 1.75mm

● Items listed above usually ex stock.

Other thicknesses and sizes available, please contact sales office for your requirements

QUALITY ASSURED PRODUCTS WITH FULL TRACEABILITY

Care should be taken in selecting the most suitable quality for each application. Advice is available but final responsibility remains with the customer.