

Natural NR/SBR

SPECIFICATION SHEET

Grade	N13	
Colour	BLACK	
Elastomer	NR/SBR	
Quality	CIRCULAR STUD	
Hardness Shore A ± 5	70°	ISO 7619-1
SG (g/cm ²)	1.50	ISO 2781
Tensile (N/mm ²)	3.5	ISO 37
Elongation %	300	ISO 37
Compression %	43	ISO 37
Tear Strength	12	ISO 34-1
Abrasion mm ³	480	ISO 37
Temperature (°C) from	-20	
Temperature (°C) to	70	

Thicknesses available

Roll Tolerances

Width tolerance:	+/- 2%	ISO 3302 SW1	3mm	1.22 x 10m	
Length tolerance:	+/- 2%	ISO 3302 SW1			
0.5– 1mm	+/- 0.2mm				
1.5mm –3mm	+/- 0.3mm				
4mm—5mm	+/- 0.4mm				
6mm	+/- 0.5mm				
8mm	+/- 0.7mm				
10mm—15mm	+/- 1mm				
20mm	+/- 1.4mm				
25mm	+/- 1.75mm				

 Items listed above usually ex stock.

Other thicknesses and sizes available, please contact sales office for your requirements

QUALITY ASSURED PRODUCTS WITH FULL TRACEABILITY

Care should be taken in selecting the most suitable quality for each application. Advice is available but final responsibility remains with the customer.