



Natural NR/SBR

SPECIFICATION SHEET

| | | |
|------------------------------|--------------|------------|
| Grade | N28 | |
| Colour | BLACK | |
| Elastomer | NR/SBR | |
| Quality | CHECKERPLATE | |
| Hardness Shore A ± 5 | 65° | ISO 7619-1 |
| SG (g/cm ²) | 1.5 | ISO 2781 |
| Tensile (N/mm ²) | 3.5 | ISO 37 |
| Elongation % | 300 | ISO 37 |
| Compression % | 43 | ISO 37 |
| Tear Strength | | ISO 34-1 |
| Abrasion mm ³ | | ISO 37 |
| Temperature (°C) from | -20 | |
| Temperature (°C) to | 70 | |

Roll Tolerances

Thicknesses available

| | | |
|-------------------|--------|--------------|
| Width tolerance: | +/- 2% | ISO 3302 SW1 |
| Length tolerance: | +/- 2% | ISO 3302 SW1 |

3mm .1.22m and
1.4m x 10m



Thickness

| | |
|------------|------------|
| 0.5– 1mm | +/- 0.2mm |
| 1.5mm –3mm | +/- 0.3mm |
| 4mm—5mm | +/- 0.4mm |
| 6mm | +/- 0.5mm |
| 8mm | +/- 0.7mm |
| 10mm—15mm | +/- 1mm |
| 20mm | +/- 1.4mm |
| 25mm | +/- 1.75mm |

● Items listed above usually ex stock.

Other thicknesses and sizes available, please contact sales office for your requirements

QUALITY ASSURED PRODUCTS WITH FULL TRACEABILITY

Care should be taken in selecting the most suitable quality for each application. Advice is available but final responsibility remains with the customer.