



Natural NR/SBR

SPECIFICATION SHEET

Grade	N55	
Colour	BLACK	
Elastomer	NR/SBR	
Quality	GRIP TOP MATTING	
Tensile (KGF/CM ³)	30	ISO 37
Elongation %	150	ISO 37
Temperature (° C) from	-40	
Temperature (°C) to	80	

Grip top rubber matting used for various applications such as conveyor belts horseboxes, ramps. Made from NR/SBR with a rough moulded top (the anti slip surface is ideal for steep inclined/declined applications) and either a 1 or 2 ply insertion made from ep polyester/polyamide fabric.

EP8o fabric insertion tensile strength (50 x 200mm):-

Longitudinal (kgf min)	500
Transversal (kgf min)	250

Roll Tolerances

Width tolerance:	+/- 2%	ISO 3302 SW1
Length tolerance:	+/- 2%	ISO 3302 SW1

Thicknesses available

6mm 1ply and 2 ply 1.22m and 1.5m ●
Rolls 50m long

Thickness

0.5– 1mm	+/- 0.2mm
1.5mm –3mm	+/- 0.3mm
4mm—5mm	+/- 0.4mm
6mm	+/- 0.5mm
8mm	+/- 0.7mm
10mm—15mm	+/- 1mm
20mm	+/- 1.4mm
25mm	+/- 1.75mm

Cut lengths available Telephone sales office for

● Items listed above usually ex stock.

Other thicknesses and sizes available, please contact sales office for your requirements

QUALITY ASSURED PRODUCTS WITH FULL TRACEABILITY

Care should be taken in selecting the most suitable quality for each application. Advice is available but final responsibility remains with the customer.