



# Neoprene CR/SBR

## SPECIFICATION SHEET

Grade	C17	
Colour	BLACK	
Elastomer	CR/SBR	
Quality	FLAME RETARDANT	
Hardness Shore A ±5	65°	ISO 7619-1
SG (g/cm <sup>2</sup> )	1.45	ISO 2781
Tensile (N/mm <sup>2</sup> )	12	ISO 37
Elongation %	450%	ISO 37
Compression %		ISO 37
Tear Strength	20	ISO 34-1
Abrasion mm <sup>3</sup>		ISO 37
Temperature (°C) from		
Temperature (°C) to		

Roll Tolerances

Width tolerance:	+/- 2%	ISO 3302 SW1
Length tolerance:	+/- 2%	ISO 3302 SW1

Thicknesses available

1mm to 6mm    1.4m x10m

8mm to 25mm    1.4m x 5m

32mm, 38mm, 40mm and  
1m x 1m

Thickness

0.5– 1mm	+/- 0.2mm
1.5mm –3mm	+/- 0.3mm
4mm—5mm	+/- 0.4mm
6mm	+/- 0.5mm
8mm	+/- 0.7mm
10mm—15mm	+/- 1mm
20mm	+/- 1.4mm
25mm	+/- 1.75mm

● Special order only subject to minimum order quantities

Other thicknesses and sizes available, please contact sales office for your requirements

QUALITY ASSURED PRODUCTS WITH FULL TRACEABILITY

Care should be taken in selecting the most suitable quality for each application. Advice is available but final responsibility remains with the customer.