

# Polycarbonate Sheet

## SPECIFICATION SHEET

Code	P60	
Colour	GLASS/CLEAR	
Product	POLYCARBONATE SHEET	
SG (g/cm <sup>3</sup> )	1.2	
Tear Strength to yield point	63 N/mm <sup>2</sup>	ISO 527
Elasticity Modulus under tension	2360 N/mm <sup>2</sup>	ISO 527
Flamability	UL94 V2	
Specific Volume Resistance	10 <sup>15</sup> Ohm/cm	IEC 93
Surface Resistance	10 <sup>15</sup> Ohm	IEC 93
Dielectric Strength	30 kV/mm	IEC 243
Total Luminous Transmittance	87.8%	

### Key Points

- High Impact Resistance
- Good heat resistance
- Glass Clear Finish
- Good electrical properties
- UL94 V2 flame retardant product
- SVHC and REACH Complaint
- Recyclable

#### Thicknesses available

3mm to 6mm    1220mm x  
2440mm

● Items listed above usually ex stock.

Other thicknesses and sizes may be available, subject to minimum order quantity. Please contact sales office for your requirements

#### QUALITY ASSURED PRODUCTS WITH FULL TRACEABILITY

Care should be taken in selecting the most suitable quality for each application.  
Advice is available but final responsibility remains with the customer.