

EPDM

SPECIFICATION SHEET

Grade	E78	
Colour	BLACK	
Elastomer	EPDM	
Quality	WRAS APPROVED 1904538	
Hardness Shore A ± 5	70°	ASTM D2240
SG (g/cm ³)	1.15	ISO 2781
Tensile (MpA)	12	ISO 37
Elongation %	400	ISO 37
Compression after 22h	25	ISO 815-1
Tear Strength (N/mm)	35	ISO 34-1
Temperature (° C) from	-40	
Temperature (°C) to	120	

Roll Tolerances

Width tolerance:	+/- 2%	ISO 3302 SW1
Length tolerance:	+/- 2%	ISO 3302 SW1

Thicknesses available

1mm to 6mm	1.62m x10m
8mm to 25mm	1.4m x 5m

Thickness

0.5– 1mm	+/- 0.2mm
1.5mm –3mm	+/- 0.3mm
4mm—5mm	+/- 0.4mm
6mm	+/- 0.5mm
8mm	+/- 0.7mm
10mm—15mm	+/- 1mm
20mm	+/- 1.4mm
25mm	+/- 1.75mm

32mm, 38mm,	1m x 1m
40mm and	
52mm	

● Items listed above usually ex stock.

Other thicknesses and sizes available, please contact sales office for your requirements

QUALITY ASSURED PRODUCTS WITH FULL TRACEABILITY

Care should be taken in selecting the most suitable quality for each application.
Advice is available but final responsibility remains with the customer.